



PeakTech
Prüf- und Messtechnik GmbH
Gerstenstieg 4
DE 22926 Ahrensburg

Phone: 0049 4102 42343/44
Fax: 0049 4102 43416

[Products](#) [Power Supplies](#) [Linear 2 CH power supplies](#) [PeakTech® 6060](#)

PeakTech® 6060 PROD-ID: P 6060

[BACK](#)

Regulated Dual Power Supply, 2 x 0 - 30 V/2 x 0 - 10 A, 5 V/3 A fixed

Regulated dual power supply for built-in into 19" racks, is ideal for service centers, schools and industry. 3 digit 14 mm blue LED-displays enables the user to read the fixed values very fast and precise. 4 mm safety jacks and as well as 19" metal cabinet are main features of this new power supply. The unit provides 2 adjustable outputs for constant voltage and current, which can be connected in parallel or in series. That means max. output voltage 60 V (in series) and max. output current in parallel 20 A DC.

- 2 adjustable outputs and one 5 V fixed output
- Output enable/disable control
- Safety: EN 61010-1
- Accessories: power cable, operation manual



MANUAL

[PeakTech_6060_12_2015.pdf \(495.4 kB\)](#)

PICTURES

[6060_L.jpg \(92.8 kB\)](#)

[6060_R.jpg \(100.1 kB\)](#)

Output voltage	2 x 0 - 30 V; 5 V/3 A fixed
Output current	2 x 0 - 10 A
Residual ripple U	2 mV < 3 A; 5 mV > 3 A; 10 mV fixed output
Residual ripple I	3 mA
Accuracy	± 0, 2 % rdg. + 2 dgt. (Voltmeter); ± 1,0 % rdg. + 2 dgt. (Amperemeter)
Operation voltage	115 V / 230 V AC; 50/60 Hz
Dimensions (WxHxD)	19" 3 HE-System-housing, 482 x 140 x 430 mm
Weight	18 kg
EAN-13	4250569401442

